

Applications areas

- * wall and ceiling surfaces
- * interior plaster and woodchip wallpaper
- * gypsum and gypsum plasterboards

Properties

- * Solvent-free
- * good covering
- * EN 13300: Wet scrub resistance class 4
Contrast ratio class (coverage) class 3 at 5-6 m²/ltr.

Application tips

- * before use always read the label
- * before use stir well
- * suitable for rolling, painting and spraying
- * recommended tools: paint roller, flat or radiator brush
- * do not use by temperatures under + 5 °C
- * the substrate has to be hard, dry, clean and stable
- * old, not stable paints have to be removed
- * sanding or sucking substrates have to be pretreated with Teifgrund LF.
Tip: a sucking substrate can be recognized when the substrate turns dark when water is applied.
- * can be tint with all usual tinting colors
- * cleaning of tools immediately after using, with water and soap

Application Technology

- * the first coat can be thinned with maximum 10 % water
- * the finish coat undiluted
Tip: During breaks the working equipment should be left in the paint or should be wrapped in a plastic bag

Drying (by 20 °C/ 65 % relative air humidity)

- * touch dry after about 2-3 hours
- * can be recoated after about 8 hours

barcode

address

green point sign

put only empty containers to recycling.

Renolin
Wand- und Deckenfarbe

MAT

Safety instructions

if medical advice is necessary, show product drum or label.
Keep away from children. Before use always read the label.
Dispose of contents / container to a collection point for hazardous waste or special waste in accordance with local, regional, national and / or international regulations.

Supplementary information (EU)

Contains BENZISOTHIAZOLINONE, METHYLCHLOROISOTHIAZOLINONE (AND) METHYLISOTHIAZOLINONE. Can cause allergic reactions.
Safety data sheet available on request.

Advice for isothiazolinone allergy sufferers: Tel. No. 04124-606-188.

General informations

should be stored cool but frost-protected. Do not use by temperatures under + 8 °C , do not use in high heat (sunlight).
do not inhale spray mist. When grinding use dust filter P2.
Eating, drinking and smoking during use of color should be avoided.
During and after application and drying ensure for good ventilation.
In contact with eyes or skin, immediately rinse thoroughly with water.
Do not let it end up in the sewerage, waters or earth. Even when working with low-emission paints the usual protective measures must be observed. Unopened best before: see separate imprint!
Already opened drum use up in nearest time. Please note the application and processing instructions in our product information as well as the current safety data sheet, available at your dealer.
Please secure this drum during transport against overturning and leakage!

VOC-EU-limit value for this product category A/a (Wb): 30 g/l (2010).
this product contains maximum 30 g/l VOC.

Ingredients

acrylate-copolymerdispersion, fillers, water, additives, preservatives.

10 L for about 60 m²

at single coat, depending of substrate!